

Repository Function DESTROY

Description

Method for destroying an entity. Entities used by it (such as window events inside windows) are not destroyed. Use the [TDESTROY](#) method to destroy an entity and entities inside it.

Syntax

object = **Repository**("DESTROY", *entID*)

Parameters

The **EXECUTE** method has the following parameters.

Parameter	Description
<i>Message</i>	DESTROY
<i>entID</i>	<i>entID</i> consists of four elements, which are '*' (asterisk) delimited:
	• Application name • Type ID • Class ID • Entity name

Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

null

Note: Always call the [Get_Status function](#) after calling *Repository*.

See also

[Repository\(\)](#) function, [TDESTROY](#) method, [Get_Repos_Entities\(\)](#).

Example

```
/* Destroy the CENTERWINDOW_BACKUP stored procedure */
Declare Function Repository, Get_Status
AppID = @APPID<1>  ;* current application
TypeID = "STPROC"  ;* OpenInsight stored procedures
ClassID = ""       ;* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW_BACKUP'

entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("DESTROY", entid)
* test result
If Get_Status(ErrCode) then
  call msg(@window, 'Error Message returned: ' : ErrCode)
end
```