

Repository Function GETSHAREABLE

Description

Method for getting the shareable flag for an entity.

Syntax

```
retval = Repository("GETSHAREABLE" , entID)
```

Parameters

The **GETSHAREABLE** method has the following parameters.

Parameter	Description
Message	"GETSHAREABLE"
entID	entID consists of four elements, which are '*' (asterisk) delimited:
	• Application name • Type ID • Class ID • Entity name
	Methods are executed as follows: if class specific, execute at the class level; if type specific, execute at the type level; otherwise, execute the method.

Returns

The shareable flag (1 or 0) of the entity.

Note: Always call the [Get_Status function](#) after calling Repository.

See also

[Repository\(\) function](#), [SETSHAREABLE Method](#), [Get_Repos_Entities\(\)](#).

Example

```
/* Get the shareable flag or the CENTERWINDOW stored procedure into the variable called result */
Declare Function Repository, Get_Status
AppID = @APPID<1>  ;* current application
TypeID = "STPROC"  ;* OpenInsight stored procedures
ClassID = ""       ;* Not Applicable
Stored_Proc_Name = 'CENTERWINDOW'
entid = AppID : '*' : TypeID : '*' : ClassID : '*' : Stored_Proc_Name

result = Repository("GETSHAREABLE", entid)
/* result now contains the shareable flag of CENTERWINDOW in Field 1. */
If Get_Status(ErrCode) then
    call msg(@window, 'Error Message returned: ' : ErrCode)
end
```