

# Set\_Env Routine

## Description

Defines the value of an environment attribute or list of attributes for the current database.

## Syntax

**Set\_Env** (*attributelist*, *valuelist*, *transactflag*)

## Parameters

The Set\_Env routine has the following parameters.

| Parameter            | Description                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>attributelist</i> | One or more attribute identifiers from the list of attributes in the table following the description of this command.                                                                                                                                                                                                                                                           |
| <i>valuelist</i>     | Specifies a value for each attribute identifier defined in <i>attributelist</i> .                                                                                                                                                                                                                                                                                               |
| <i>transactflag</i>  | If true (1), all values in <i>valuelist</i> must be valid or no attributes are set. If <i>transactflag</i> is false (0) or null, valid attributes are set and invalid attributes are ignored. A column is returned for each attribute in <i>attributelist</i> . If a valid value is provided, the column is true (1). If an invalid value is provided, the column is false (0). |

## See also

[Get\\_Env](#), [ENVIRON\\_CONSTANTS](#) [insert record](#)

## Remarks

For examples of finding the current environment settings, see [Get\\_Env](#).

## Example (disabling the debugger)

```
/* in this example, the debug statement does not go to the debugger
   because the debugger is disabled */
$insert environ_constants
declare subroutine set_env
on_off = 0
t_flag = 1
set_env(ENV_DEBUGGER_ENABLED$, on_off, t_flag)
debug
```