

Set Printer LOADDDOC

Description

The LOADDDOC message is used to load a previously created report that was saved with the INIT message or to retrieve an archived report.

Parameters

Parameter	Description of Fields	Comments	Default
Parm1	<1> Report Name	An @vm-delimited list of filenames. Reports saved using the OIPI format should include the full path. Reports saved using the ARCHIVE message need only the report name.	""
	<2> Archive.	Boolean. If true will load the report from the ARCHIVE.	"" (False)

Example

```
*The following example shows how to use the LOADDDOC message to retrieve a  
*previously created report or Archived report.*/
```

```
* Create report and save as c:\savefile\smpreport.rpt
```

```
declare function Set_Printer
```

```
* Create a saved OIPI Report
```

```
File = "Sample":@fm:"":@fm:10:@fm:"c:\savefile\smpreport.rpt"  
stat = Set_Printer("INIT",FILE,"",""," ",2) ;* Start printing  
text = "This is a test line" stat = Set_Printer("TEXT", text)  
stat = Set_Printer("TERM")
```

```
* Create an Archive Report
```

```
File = "Sample":@fm:"":@fm:11:@fm:"smpreport"  
stat = Set_Printer("INIT",FILE,"",""," ",2) ;* Start printing  
text = "This is a test line" stat = Set_Printer("TEXT", text)  
stat = Set_Printer("TERM")
```

```
*Load report - Only valid if originally saved.
```

```
stat = Set_Printer("INIT","",""," ",2)  
stat = Set_Printer("Loaddoc","C:\savefile\smpreport.rpt")  
stat = Set_Printer("TERM")
```

```
*Load from Archive - Only valid if originally Archived
```

```
stat = Set_Printer("INIT","",""," ",2)  
stat = Set_Printer("Loaddoc","smpreport",1)  
stat = Set_Printer("TERM")
```

Example 2

```
* Create 2 reports and load them into one preview window

* Create a saved OIPI Report
file = "Sample":@fm:"":@fm:10:@fm:"c:\savefile\smpreport.rpt"
stat = Set_Printer("INIT",FILE,"","",2) ;* Start printing
text = "This is a test line"
stat = Set_Printer("TEXT", text)
stat = Set_Printer("TERM")

* Create another saved OIPI Report
file = "Sample":@fm:"":@fm:10:@fm:"c:\savefile\smpreport1.rpt"
stat = Set_Printer("INIT",FILE,"","",2) ;* Start printing
text = "This is a test line in a separate report!"
stat = Set_Printer("TEXT", text)
stat = Set_Printer("TERM")

* Load both reports
stat = Set_Printer("INIT","","",2)
reports = "C:\savefile\smpreport.rpt":@vm:"C:\savefile\smpreport1.rpt"
stat = Set_Printer("LOADDOC",reports)
stat = Set_Printer("TERM")
```