

Set Printer STARTTABLE

Description

The STARTTABLE message is used in conjunction with the ADDTABLE and TABLECELL messages. If formatting is to be done upon a ttable then the STARTTABLE message must be sent prior to the ADDTABLE.

Parameters

There are no parameters for this message.

Example

```
Set_Printer("INIT", "", "", "", 1, 2)

Set_Printer("STARTTABLE")

colFormat = '<_1440':@vm:<_1440':@vm:<_1440'
colHeader = 'Column 1':@vm:'Column 2':@vm:'Column 3'
data = ''
for i = 1 to 30
  data<-1> = 'Col 1 - ':i:@vm:'Col 2 - ':i:@vm:'Col 3 ':i
next i

Set_Printer("ADDTABLE", colFormat, colHeader, data, ',', ',', ',', ',')

* Set First Column to Bold
Set_Printer("TABLECELL", 25:@fm:1:@fm:1:@fm:30:@fm:1:@fm:1)

* Set Second Column to Underline
Set_Printer("TABLECELL", 27:@fm:1:@fm:2:@fm:30:@fm:2:@fm:1)

Set_Printer("ENDTABLE")

Set_Printer("TERM")
```

See also

[ADDTABLE Set_Printer\(\) Message](#), [ENDTABLE Set_Printer\(\) Message](#), [TABLECELL Set_Printer\(\) Message](#)