

Appendix D: \$INSERT Record MAPI EQUATES Insert Record

```
compile insert MAPI_EQUATES
* used by MAPILogon(), MAPISendMail(), MAPISaveMail(), MAPIDetails(), MAPIDeleteMail(),
*      MAPIAddress(), MAPILogoff(), MAPIOpenMail()
EQU MAPI_LOGON_UI$      to 1 ;* Display logon dialog
EQU MAPI_NEW_SESSION$   to 2 ;* Do not use default session
EQU MAPI_DIALOG$        to 8 ;* Display a send note dialog
EQU MAPI_UNREAD_ONLY$   to 32 ;* Only unread messages
EQU MAPI_ENVELOPE_ONLY$ to 64 ;* Only header information
EQU MAPI_PEEK$          to 128 ;* Do not mark as read
EQU MAPI_GUARANTEE_FIFO$ to 256 ;* Retain date order
EQU MAPI_BODY_AS_FILE$  to 512 ;* Attach body as file
EQU MAPI_AB_NOMODIFY$   to 1024 ;* Do not update address book
EQU MAPI_SUPPRESS_ATTACH$ to 2048 ;* Do not return files
EQU MAPI_FORCE_DOWNLOAD$ to 4096 ;* Download new mail
EQU MAPI_UNREAD$        to 1 ;* Message has not been read
EQU MAPI_RECEIPT_REQUESTED$ to 2 ;* Notify when message has been received
EQU MAPI_SENT$          to 4 ;* Message has been sent

* Maximum length of message id
EQU MAX_ID$ TO 64

* Maximum length of message parts returned
EQU MAX_SUBJECT$ TO 256
EQU MAX_FROM$ TO 256
EQU MAX_TO$ TO 1024
EQU MAX_CC$ TO 1024
EQU MAX_BCC$ TO 1024
EQU MAX_DATE$ TO 32
EQU MAX_TEXT$ TO 32767
EQU MAX_CLASS$ TO 256
EQU MAX_FLAG$ TO 16
EQU MAX_FILE$ TO 1024
EQU MAX_PATH$ TO 4096
EQU MAX_POSITION$ TO 1024

* Position in structure of message parts returned
EQU POS_SUBJECT$ TO 1
EQU POS_FROM$ TO 2
EQU POS_TO$ TO 3
EQU POS_CC$ TO 4
EQU POS_BCC$ TO 5
EQU POS_DATE$ TO 6
EQU POS_TEXT$ TO 7
EQU POS_TYPE$ TO 8
EQU POS_CLASS$ TO 8
EQU POS_FLAG$ TO 9
EQU POS_FILE$ TO 10
EQU POS_PATH$ TO 11
EQU POS_POSITION$ TO 12
Source Date: 17:49:07 31 JAN 1996 Build ID: OINOTES*3.1.40 Level: 3.1
```