

U2 Functions in OI U2 Btree Extract subroutine

Description

This subroutine is similar to the Linear Hash Btree.Extract. Searches one or more indexes for data matching the search criteria passed in. Returns the keys to rows having matching data.

Syntax

U2_Btree_Extract(Search_String, Filename, Dictvar, Keys, Opts, Status)

Parameters

The subroutine has the following parameters:

Parameter	Description						
Search_String	The search criteria to use. See Btree.Extract for syntax. Note: This is currently an exact match extract.						
Filename	Pass the name of the file to be searched.						
Dictvar	Pass the file handle for the dictionary of the specified file.						
Keys	Returns row keys for all rows that satisfy the criteria in Search_String. Multiple keys are delimited with value marks.						
Opts	For U2_Btree_Extract this parameter should be null.						
Status	Error codes are returned in the Status parameter. After execution, keys contains a list of keys matching the search criteria. Status returns one of several possible values, depending on the success of the search process. <table><tr><th>Value</th><th>Meaning</th></tr><tr><td>0</td><td>The search was successful. All possible keys were returned in keys.</td></tr><tr><td>-1</td><td>The search failed, for reasons other than no keys found. This occurs, for example, when a specified column does not have a Btree index.</td></tr></table>	Value	Meaning	0	The search was successful. All possible keys were returned in keys.	-1	The search failed, for reasons other than no keys found. This occurs, for example, when a specified column does not have a Btree index.
Value	Meaning						
0	The search was successful. All possible keys were returned in keys.						
-1	The search failed, for reasons other than no keys found. This occurs, for example, when a specified column does not have a Btree index.						

See also

[Btree.Extract](#), [U2 Functions](#)