SRP_JsonX_Members

Gets all an object's member names.

Syntax

```
Members = SRP_JsonX_Members(Path, Delim)
```

Returns

The object's member names.

Parameters

Parameter	Description
Path	Path to an object whose member names to get.
Delim	The delimiter to use in the final member list. **Optional.** *Default is @FM*

Remarks

SRP_JsonX_Members gets the list of member names of the object pointed to by Path. See Paths for more details. The list is not guaranteed to be in any particular order. By default, the list is @FM delimited, but you can use the Delim parameter to set your preferred delimiter.

Examples

```
$insert SRPJSONX

Json  = '{'
Json := '    "employees": ['
Json := '        {'
Json := '            "firstname": "John",'
Json := '            "lastname": "Doe",'
Json := '            "age": 21'
Json := '        },'
Json := '        {'
Json := '            "firstname": "Anna",'
Json := '            "lastname": "Smith",'
Json := '            "age": 32'
Json := '        },'
Json := '        {'
Json := '            "firstname": "Peter",'
Json := '            "lastname": "Jones",'
Json := '            "age": 43'
Json := '        }'
Json := '    ],'
Json := '    "nums": [1, 2, 3, 4, 5, 6, 7, 8, 9, 10],'
Json := '    "active": true,'
Json := '    "alwaysnull": null,'
Json := '    "alwaysstring": "4.321"'
Json := '}'

SRP_JsonX_Parse('MyDocument', json)
        Members = SRP_JsonX_Members('employees[2]', ',')
SRP_JsonX_End()
```