

SRP_JsonX_Members

Gets all an object's member names.

Syntax

```
Members = SRP_JsonX_Members(Path, Delim)
```

Returns

The object's member names.

Parameters

Parameter	Description
Path	Path to an object whose member names to get.
Delim	The delimiter to use in the final member list. Optional. <i>Default is @FM</i>

Remarks

SRP_JsonX_Members gets the list of member names of the object pointed to by Path. See [Paths](#) for more details. The list is not guaranteed to be in any particular order. By default, the list is @FM delimited, but you can use the Delim parameter to set your preferred delimiter.

Examples

```
$insert SRPJSONX

Json = '{
Json := '      "employees": ['
Json := '        {
Json := '            "firstname": "John", '
Json := '            "lastname": "Doe", '
Json := '            "age": 21'
Json := '        }, '
Json := '        {
Json := '            "firstname": "Anna", '
Json := '            "lastname": "Smith", '
Json := '            "age": 32'
Json := '        }, '
Json := '        {
Json := '            "firstname": "Peter", '
Json := '            "lastname": "Jones", '
Json := '            "age": 43'
Json := '        }
Json := '    ], '
Json := '    "nums": [1, 2, 3, 4, 5, 6, 7, 8, 9, 10], '
Json := '    "active": true, '
Json := '    "alwaysnull": null, '
Json := '    "alwaysstring": "4.321"'
Json := '}'

SRP_JsonX_Parse('MyDocument', json)
    Members = SRP_JsonX_Members('employees[2]', ',')
SRP_JsonX_End()
```