

# SRP\_HashTable Remove

Removes a key and it's paired value from an SRP Hash Table.

## Syntax

```
SRP_HashTable( "Remove" , Handle , Key )
```

## Parameters

Parameter	Description
Handle	Handle to an existing SRP Hash Table ( <b>REQUIRED</b> )
Key	The key to remove ( <b>REQUIRED</b> )

## Remarks

The Remove service removes a key and its paired value from a SRP Hash Table. If the key doesn't exist, then nothing happens.

## Examples

```
// Create a case-insensitive hash table
Handle = SRP_HashTable( "Create" )

// Add some entries
SRP_HashTable( "Set" , Handle , "Amazon" , "http://www.amazon.com" )
SRP_HashTable( "Set" , Handle , "Google" , "http://www.google.com" )
SRP_HashTable( "Set" , Handle , "Revelation" , "http://www.revelation.com" )
SRP_HashTable( "Set" , Handle , "SRP" , "http://www.srpcs.com" )
SRP_HashTable( "Set" , Handle , "Yahoo" , "http://www.yahoo.com" )
SRP_HashTable( "Set" , Handle , "Empty" , "" )

// The key exists
Exists = SRP_HashTable( "Contains" , Handle , "SRP" )

// Remove one
SRP_HashTable( "Remove" , Handle , "SRP" )

// The key no longer exists
Exists = SRP_HashTable( "Contains" , Handle , "SRP" )

// Release it
SRP_HashTable( "Release" , Handle )
```