

AddAppts

Adds new appointments to the control.

Syntax

```
Send_Message(CtrlEntId, "OLE.AddAppts", Appts)
```

Parameters

Parameter	Description
Appts	@FM delimited list of appts

Remarks

The AddAppts method adds new appointments to the control. This method takes a single argument: an @FM delimited array, with each field containing the following values:

Position	Name	Type	Description
<x, 1>	Calendar Key	Text	The unique key of the calendar to contain this appointment.
<x, 2>	Key	Text	The unique key for this appointment. No two appointments can have the same key, even if they are in different calendars.
<x, 3>	Start	DateTime	The date and time, in OI internal format, that the appointment begins.
<x, 4>	End	DateTime	The date and time, in OI internal format, that the appointment ends.
<x, 5>	Subject	Text	The short summary describing the appointment.
<x, 6>	Body	Text	The details of the appointment.
<x, 7>	Location	Text	The brief description of the appointment's location.
<x, 8>	Label Key	Text	The unique key of a previously defined label, which will categorize and colorize this appointment.
<x, 9>	Busy Status	Option	One of four options: "Free", "Tentative", "Busy", or "OutOfOffice".
<x, 10>	Importance	Option	One of three options: "Low", "Normal", or "High".
<x, 11>	Is Meeting Flag	Boolean	Determines if the appointment is a meeting.
<x, 12>	Is Private Flag	Boolean	Determines if the appointment is private.

NOTE: Define your labels *before* you add your appointments.

Example

```
// Add one more appointment
Appts = ""
Appts<1, 1> = "WORK"
Appts<1, 2> = "10003"
Appts<1, 3> = IConv(OConv(Date(), "D4/"): " 3:30PM", "DT")
Appts<1, 4> = IConv(OConv(Date(), "D4/"): " 4:30PM", "DT")
Appts<1, 5> = "Staff Meeting"
Appts<1, 6> = "Weekly staff meeting"
Appts<1, 7> = "Conference Room"
Appts<1, 8> = "Urgent"
Appts<1, 10> = "High"
Appts<1, 11> = 0
Appts<1, 12> = 1
SendMessage(@Window:".OLE_CALENDAR", "OLE.AddAppts", Appts)
```