

CloseButtonColors

Color settings for all close buttons.

Usage

```
Set_Property(OLECtrlEntID, "OLE.CloseButtonColors", Array)
```

Values

Array has the following structure:

Pos	Name	Type	Description	Default
<1>	Normal State			
<1, 1>	Forecolor	Color	The color of the X when the button is in its resting state	RGB(128, 128, 128)
<1, 2>	Background	Color Fill	The background color when the button is in its resting state	None
<2>	Hot State			
<2, 1>	Forecolor	Color	The color of the X when the mouse is over the button	RGB(255, 255, 255)
<2, 2>	Background	Color Fill	The background color when the mouse is over the button	Vertical(Gradient(Red, Red), Border(Red L=10), Rounded(2))
<3>	Pressed State			
<3, 1>	Forecolor	Color	The color of the X when the button is down	RGB(255, 255, 255)
<3, 2>	Background	Color Fill	The background color when the button is down	Vertical(Gradient(Red L=10, Red L=10), Border(Red L=10), Rounded(2))

Remarks

The CloseButtonColors property establishes the colors of all close buttons.

Example

```
// Make the buttons white on gray
Colors = ""
Colors<1, 1> = "White"
Colors<1, 2> = "None"
Colors<2, 1> = "White"
Colors<2, 2> = "Gray"
Colors<3, 1> = "White"
Colors<3, 2> = "DarkGray"
Set_Property(@Window:".OLE_TREE", "OLE.CloseButtonColors", Colors)
```

See Also

[CloseButtonBehavior](#), [CloseButtonConditions](#), [ItemCloseButton](#), and [DefCloseButton](#)