

RTI_List Function

Description

The RTI_List function is a utility that helps in the use and management of saved lists in the SYSLISTS table.

Syntax

returnvalue = RTI_List(<function>, <listID> [,<param1>] [,<param2>] [,<param3>] [,<param4>])

Parameters

The function has the following parameters:

Parameter	Description	
<i>function</i>	A valid RTI_List function: READ, DELETE.	
<i>listID</i>	Name of the saved list (or Key ID) in the SYSLISTS table.	
<i>param1...</i>	Each method has different parameter requirements.	
<i>param4</i>		
functions	Value	Description
	READ	Reads all the Key IDs from the indicated saved list and returns them as an @FM delimited array.
	DELETE	Deletes the indicated saved list.
Parameters	Function	Parameters
	READ	<i>bAutoDelete</i> - Flag that determines if the saved list should be deleted automatically after the READ function is invoked.
	DELETE	Null

Returns

Method	Return Value
READ	An @fm-delimited array of Key IDs.
DELETE	Null

Examples

```
* READ Example
DECLARE FUNCTION RTI_LIST, RTI_CREATEGUID
myID = RTI_CREATEGUID("b") ;* MAKE A GUID IN BASE64 FORMAT
CALL RLIST(selStmt, 4, myID, "", "")
fullList = RTI_LIST("READ", myID)

* DELETE Example
CALL RTI_LIST("DELETE", myID)
```