RTI_List Function

Description

The RTI_LIst function is a utility that helps in the use and management of saved lists in the SYSLISTS table.

Syntax

returnvalue = **RTI_List(<function>, <listID>** *[,<param1>] [,<param2>] [,<param3>] [,<param4>]*)

Parameters

The function has the following parameters:

<table>
<tr><th>Parameter</th><th>Description</th></tr>
<tr><td>function</td><td>A valid RTI_List function: READ, DELETE.</td></tr>
<tr><td>listID</td><td>Name of the saved list (or Key ID) in the SYSLISTS table.</td></tr>
<tr><td>param1...</td><td>Each method has different parameter requirements.</td></tr>
<tr><td>param4</td><td></td></tr>
<tr><td>functions</td><td>
<table>
<tr><th>Value</th><th>Description</th></tr>
<tr><td>READ</td><td>Reads all the Key IDs from the indicated saved list and returns them as an @FM delimited array.</td></tr>
<tr><td>DELETE</td><td>Deletes the indicated saved list.</td></tr>
</table>
</td></tr>
<tr><td>Parameters</td><td>
<table>
<tr><th>Function</th><th>Parameters</th></tr>
<tr><td>READ</td><td>bAutoDelete - Flag that determines if the saved list should be deleted automatically after the READ function is invoked.</td></tr>
<tr><td>DELETE</td><td>Null</td></tr>
</table>
</td></tr>
</table>

Returns

Method	Return Value
READ	An @fm-delimited array of Key IDs.
DELETE	Null

Examples

```
* READ Example
DECLARE FUNCTION RTI_LIST, RTI_CREATEGUID
myID = RTI_CREATEGUID("b") ;* MAKE A GUID IN BASE64 FORMAT
CALL RLIST(selStmt, 4, myID, "", "")
fullList = RTI_LIST("READ", myID)

* DELETE Example
CALL RTI_LIST("DELETE", myID)
```